



ePad LS is an elite, full-color LCD electronic signature capture device for customer-facing applications with cross-selling opportunities. The large, robust color screen displays HTML documents in multiple fonts, allows for scrolling text, customer affirmation, signer and visual feedback, and targeted cross-marketing and sales initiatives.

The ePad LS can be deployed enterprise-wide and gives users the power to leverage their in-branch real estate with a multi-functional device that eliminates the need for numerous pin-pads and keyboards on the desktop.

The ePad LS captures and encrypts legally-binding esignatures and offers the ability to assign a unique serial identification number to the host computer. ePad LS comes bundled with IntegriSign® Desktop for esigning Microsoft Word, Excel, and Adobe Acrobat documents out of the box.

**Key Features:**

- Full-color LCD • Displays HTML documents • Enables cross-marketing during the esigning process
- Offers plug-ins for Microsoft Word, Excel, and Adobe Acrobat
- Leverages in-branch real estate and eliminates the need for numerous desktop devices
- Assigns a unique serial ID number to the host computer
- Bundled with IntegriSign Desktop Software; upgradeable to IntegriSign Pro • Produces legally-binding esignatures

**Product Specifications**

■ **Signing Surface/Tools**

Touchpad Technology	Highly reliable ITO resistive LCD touchpad
LCD Technology	Full-color LCD with CCFL backlight
Touchpad Resolution	900 x 1200 ppi (points per inch)
Display Resolutions	320 x 240
Protective Screen	Removable/field replaceable signature surface
Actuator Type	Tethered passive stylus

■ **Technical Specs**

Power Source	110-240V AC, 50-60Hz, 2.4 AMPS
Communications Interface	USB 1.1 with optional USB hub
Encryption	AES 256 bit, optional
System Requirements	Windows 2000/XP, Vista
Report Rates	100, 200 and 400 counts per seconds
Weight	0.67 kg (1.48lbs)
Device Dimensions	212.7mm long x 187.63mm wide x 50mm high (8.37" x 7.39" x 2")
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-15°C to 70°C (5°F to 158°F)
Operating Humidity	10-80% RH, non-condensing
Storage Humidity	85% RH Max, non-condensing
Warranty	1 year

eSIGN Anywhere™

