



Four Terminal Bare Element Resistors

60 Series Four Terminal Shunt Resistors



Series	Wattage	Resistance Range (Ω)*	Amps max.	Tolerance*
610	1W	0.002-0.050	32	1%
650	5W	0.002-0.005	100	1%

*Standard; others available

Ohmite's Four Terminal Bare Element Resistors provide ultra low resistance values (to 0.0005 Ω) for relatively high current requirements, with the advantages of a Kelvin configuration and PC Board mounting capability.

These resistors are specifically designed for low resistance applications requiring the highest accuracy and temperature stability. This Four Terminal version of Ohmite's 60 Series Resistor is specially designed for use in a Kelvin configuration, in which a current is applied through two opposite leads and sensing voltage is measured across the other two leads.

The Kelvin configuration enables the resistance and temperature coefficient of the leads to be effectively eliminated. The four terminal design also results in a lower Temperature Coefficient of Resistance and lower self heating drift which may be experienced on two terminal resistors. The requirement to connect to the leads at precise test points is eliminated, allowing for tighter tolerancing on the end application.

FEATURES

- Ideal for current sensing applications
- 1% tolerance standard, others available
- Low inductance (non-inductive below 0.05 Ω)
- RoHS compliant
- Radial, self-supporting, design is ideal for PC board mounting
- High Power-to-size ratio
- Decimal marked, silicone coated (650 Series only)

SPECIFICATIONS

Material

Terminals: Tinned Copper

Resistive element: Manganin Alloy

Electrical

Operating Temperature Range: -55°C to +275°C.

Temperature Coefficient of Resistance, 0°C to 85°C: ± 50 PPM/°C, .015 Ω and higher ± 100 PPM/°C, .015 Ω and lower


Environmental Performance: Exceeds the requirements of MIL-PRF-49465

Power rating: Based on 25°C free air rating

Overload: 5 times rated wattage for 5 seconds

Thermal EMF: Less than $\pm 3\mu\text{V}/^\circ\text{C}$

Derating: Linearly from 100% @ +25°C to 0% @ 275°C



STOCK PART NUMBERS		
Ohmic value	610 Series 1 watt	650 Series 5 watt
0.002	610FPR002	650FPR002
0.005	610FPR005	650FPR005
0.010	610FPR010	-
0.015	610FPR015	-
0.020	610FPR020	-
0.025	610FPR025	-
0.036	610FPR036	-
0.050	610FPR050	-

ORDERING INFORMATION		
<p>6 1 0 F P R 0 5 0</p> <p>Series: 610, Tolerance: F=1%, D=0.5%, Wattage: 10=1.0, 50=5.0, Ohm Value: Example: R050=0.05Ω</p> <p>Terminals: Blank = 2 terminals, P = 4 terminals</p>		