

Engineering Resistor Kits

FEATURES

- Excellent for design engineering
- Fourteen different style/resistance combinations
- Resistor kits are available in a 1% tolerance
- Five resistors of each style: 70 resistors in all
- Resistors can be used in parallel or series circuits to achieve any resistance value within the resistance range
- Kits are shipped in high quality storage cases

These resistors can be calibrated for use as resistor standards. The calibration point (voltage) must be specified by the user. Contact factory for further assistance.

HI-MEG DECADE SETS: GENERAL SPECIFICATIONS

Ohmite Series	Resistance Range (Ohms)	Available Tolerances
RX-1M-1	1M - 10,000 M	1%
RX-1M-2	10M - 10,000M	1%
RX-1M-2	1M - 100,000M	5%
RX-1M-3	100M - 10,000M	1%
RX-1M-3	100M - 100,000M	5%
RX-1M-3	100M - 1,000,000M	10%


SLIM-MOX RESISTOR KITS

Ohmite Style	Resistance Range	Voltage Rating	Power Rating
SLIM-MOX102	1 Meg	5.0KV	1.0W
SLIM-MOX102	5 Meg	5.0KV	1.0W
SLIM-MOX104	5 Meg	10.0KV	1.5W
SLIM-MOX102	10 Meg	5.0KV	1.0W
SLIM-MOX108	10 Meg	20.0KV	2.5W
SLIM-MOX102	50 Meg	5.0KV	1.0W
SLIM-MOX104	50 Meg	10.0KV	1.5W
SLIM-MOX104	100 Meg	10.0KV	1.5W
SLIM-MOX108	100 Meg	20.0KV	2.5W
SLIM-MOX102	500 Meg	5.0KV	1.0W
SLIM-MOX108	500 Meg	20.0KV	2.5W
SLIM-MOX102	1,000 Meg	5.0KV	1.0W
SLIM-MOX104	1,000 Meg	10.0KV	1.5W
SLIM-MOX108	1,000 Meg	20.0KV	2.5W

MINI-MOX RESISTOR KITS

Ohmite Style	Resistance Range	Voltage Rating	Power Rating
MOX-300	1 Meg	1,000V	0.50W
MOX-200	2 Meg	500V	0.25W
MOX-400-23	5 Meg	2,500V	0.75W
MOX-300	10 Meg	1,000V	0.50W
MOX-200	20 Meg	500V	0.25W
MOX-300	30 Meg	1,000V	0.50W
MOX-400-23	50 Meg	2,500V	0.75W
MOX1125-23	100 Meg	7,500V	1.50W
MOX-400-23	200 Meg	2,500V	0.75W
MOX-300	300 Meg	1,000V	0.50W
MOX-400-23	500 Meg	2,500V	0.75W
MOX-750-23	1,000 Meg	5,000V	1.00W
MOX-750-23	2,000 Meg	5,000V	1.00W
MOX1125-23	10,000 Meg	7,500V	1.50W

“SLIM-MOX” Kit series



“MINI-MOX” Kit series

